



# ReBounce™

## FLOOR CLEANER & ENHANCER

An effective daily cleaner and enhancer that extends the life of the coating and leaves a brilliant wet-look shine.



### WHY REBOUND FLOOR CLEANER & ENHANCER:

#### EXTENDS THE LIFE OF THE COATING

Wax fortified formulation

#### HELPS MAINTAIN COATING ELASTICITY, PREVENT CRACKS AND CHIPS

Wax fortified formulation

#### ENHANCES BURNISH RESPONSE — GLOSS “POPS” BACK

High performance pH-balanced surfactant

#### EFFECTIVELY REMOVES DIRT AND SCUFFS

### DIRECTIONS

Dilute product at:

- FS/MPE 1:32 (32ml per 1 liter or 4 US oz per gallon of water) for automatic scrubber application.  
1:64 (16ml per 1 liter or 2 US oz per gallon of water) for mop-on application.
- DD 1:128 (8ml per 1 liter or 1 US oz per gallon of water) for automatic scrubber application.  
1:256 (4ml per 1 liter or 0.5 US oz per gallon of water) for mop-on application.

Dilute with water according to product instructions. Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)

### TECHNICAL DATA

<b>Description</b>	Water-based cleaner/enhancer
<b>Appearance</b>	Clear green
<b>pH</b> ASTM E70-07	9.0 (as supplied) DTC/DD: 10.5 (as supplied)
<b>Viscosity</b> <b>(Brookfield)</b> @ 68°F (20°C)	<10 centipoise
<b>Dry Time</b>	About 15 minutes
<b>VOC</b> 40 CFR Part 59 Subpart C	0.01% (as supplied) <0.01% (1:32 dilution) <0.01% (1:128 dilution) DTC/DD: 0.02% (as supplied)
<b>Non-Volatile Solids</b> ASTM D2834-95 (2008)	11% DTC/DD: 46%
<b>Fragrance</b>	Lemon-lime
<b>Slip Resistance</b> ULTM410	Meets requirements
<b>Shelf Life</b> ASTM D1791-93 (2008)	1 year
<b>Density</b> ASTM D1475-98 (2008)	8.4 lb/gal @ 68°F 1.01 kg/L @ 20°C DTC/DD: 8.6 lb/gal @ 68°F DTC/DD: 1.03 kg/L @ 20°C
<b>Freeze/Thaw</b> ASTM D3209-93 (2008)	Passes 3 cycles

SURFACES



<b>Product Code</b>	211FS	211MPE	211DTC	211D	211DD
<b>Volume</b>	2.50 US gallons	4 liters	.053 US gallon	1.06 US gallons	0.50 US gallon
<b>Shipping Package</b>	2 x 2.5 gallons	4 x 4 liters	4 x 0.53 gallons	4 x 1.06 gallons	3 x 0.50 gallons
<b>Pallet Quantity</b>	48	48	88	48	112



Floor Coating and Finishing materials as to slip resistance only. 42E6